
















نام کالا	مدل	تصویر و اندازه	خلاصه مشخصه کالا	قیمت به ریال
دستگاه DVR STAN- DA- LON- E	3504HQ		4 ch BNC, Monitor, LCD 2.5", 4 channel real time recording, Mouse, Remote Control, MJPEG, W/O HDD, Multi-port VGA playback; Forward: X4, X8; Backward: X4, X8 port RS485	2700000
	JK-913		4 CH Digital, MJPEG, timer setting for searching, USB port, 1.5" TFT, Real time record, 25 frames, Support motion-detection; alarm function	
	JK-963		2.5" LCD, Up to 4 color, Record capabilities up to 30 (NTSC) / 25 (PAL) IPS Video/audio backup to SD card or USB 2.0 storage devices, pen drive, DVD+RW, Ethernet interface, Multi-lingual Audio 2-port S-Video-port VGA-backup USB Switch on/off-port RS485	3700000
	As-804B		4ch video-4ch audio-port VGA-port LAN-Port mouse-backup USB-port RS485-port Alarm-HDD sata-3G mobile-external 12V power-remote control-menu graphic-real time Play and record-H.264 format Compression	2700000
	As-808A		8ch video-8ch audio-port VGA-port LAN-Port mouse-backup USB-port RS485-port Alarm-HDD sata-3G mobile-external 12V power-remote control-menu graphic-real time Play and record-H.264 format Compression	4000000
	3016		16ch video-16ch audio-16 loop video-port VGA-port LAN-CD/DVD support Port mouse-backup USB-port RS485-port Alarm-4HDD sata-3G mobile- power-remote control-menu graphic-real time Play and record-H.264 format Compression <b>output: 2ch</b> <b>Multiple Search Categories (Date/Time, Motion, Alarm, Manual)</b> <b>Simultaneously Live, Record, Playback, back-up and Network</b> <b>User-friendly GUI Menu, Mouse Operation</b>	8000000
	9004HS		4ch video- -port VGA-Port mouse-port RS485-port Alarm-HDD sata-remote control-real time -Play and record-mjpeg format Compression	1750000
	3204HC-11		4ch video-1ch audio-port VGA-port LAN-Port mouse-backup USB-port RS485-port Alarm-HDD sata - -remote control-menu graphic-real time Play and record-H.264 format Compression	



	3507HC		4ch video-2ch audio-portVGA-port LAN-Port mouse-backup USB-port RS485-port Alarm-HDD sata-3G mobile-external 12V power-remote control-menu graphic-real time Play and record-H.264 format Compression	
			<b>USB EXTERNAL DVR</b> 4ch video-2ch audio-	
DVR BOARD	KD-6516		6805 video Decoder 16ch video,8ch audio, TV out,H.264,200fps, resolution:640x480,640x240,320x2440	2285000
	KD-7004		6805 video Decoder 4ch video,H.264-100fps, resolution:640x480,640x240,320x2440	1185000
	KD-7008		7130 video Decoder 8ch video ,H.264,200fps,100fps, resolution:640x480,640x240,320x240 Support max 32 chvideo.windows 2000/ XP/ Vista	1635000
	AV-4000		23881 video Decoder(10BITADC)4 ch video input, 4ch Audio InputMPEG4/H.264 rate: 100fps(PAL Support up to 16channel video input windows/2000/XP	1765000
	AV-8000		23881 video Decoder(10BITADC)8 ch video input, 8ch Audio InputMPEG4/H.264 rate: 100fps(PAL Support up to 16channel video input windows/2000/XP	2465000
	18016		<b>UNISIGHT</b> 16ch video input, 16ch Audio 4CH as 4 CIFresolution real time and HD900. 8CH as CIFresolution real time.DM 645 frames lost. support to 64channel	4200000
	18008		<b>UNISIGHT</b> 8ch video input, 8ch Audio 2CH as 4 CIFresolution real times. 4CIF preview resolution real time.DM 645 NO frame lost. Support to 64channel.	3100000
	18004		<b>UNISIGHT</b> 4ch video input, 4ch Audio 4CH as 4 CIFresolution real time. 4CIF preview resolution 8CH as CIFresolution real time. real time.DM 645 NO frame lost. support to 64channel	2100000

DO MEC ANE RA	AS-9470D	 130 *130 * 110	Color Dome camera 1/3"SONY CCD 420TVL0.1Lux/F1.2 4mm Lens	490000
	C 912		Color Dome camera 1/3"SONY CCD 420TVL0.1Lux/F1.2 4mm Len	
	E232E3		<b>Vandal-proof IR dome camera 1/3"Sony CCD 420TVL 0.5Lux/F1.2 15m 3.6mm Lens</b>	580000
	AS-313A	 95*95*70	Vandal-proof IR dome camera 1/3"Sony CCD 420TVL 0Lux/F1.2 15m 3.6mm Lens	590000
	AS-313B		Vandal-proof IR dome camera 1/4"SHARP CCD 420TVL 0Lux/F1.2 15m 3.6mm Lens	490000
	<b>AS-330B</b>		<b>Vandal-proof IR vari-focal dome camera 1/3"SONY CCD 480TVL- .05Lux/F1.2 20m 3.5-8mm Lens</b>	<b>850000</b>
BOX CAM EA	AS-696A	   135*65*75	Color Box camera 1/4" SHARP CCD 420TVL 0.8Lux/F1.2	390000
	AS-692S		Color digital camera 1/4" SHARP CCD 420TVL1.2Lux/F1.2 WITHOUT LENS	420000
	AS-698A		Color box camera 1/4" SONY CCD 420TVL 0.8 Lux/F1.2 WITHOUT LENS	500000
	AS-899A		Color box camera 1/3" SONY CCD 480TVL 0.8Lux/F1.2 WITHOUT LENS	520000
	JK-2100		Color box camera 1/3" SONY CCD 480TVL 0.5Lux/F1.2 WITHOUT LENS	450000
	C232D		1/3" SONY CCD 420TVL 0.5Lux/F1.2 WITHOUT LENS WITHOUT LENS	510000
	<b>AS-3012C</b>			<b>Color box camera 1/3" SONY CCD 480TVL 0.5 Lux/F1.2</b>
	<b>AS-3012D</b>	<b>Color box camera 1/3" SONY CCD 520TVL 0.5 Lux/F1.2</b>		950000
ZOO M CAM ERA	AS-998	 <i>Day&amp;Night</i> 115*60*70	22X color zoom camera 1/3"SONY CCD 480TVL0.01Lux/F1.	
	JK-300H		22X color zoom camera 1/3"SONY CCD 480TVL0.01Lux/F1.2	950000
	979DW		Auto Focus//Auto Iris,1/4" SONY CCD 480TVL .22Xoptical zoom=F3.9- 85.8mm,SensorIR0.01Lux/F1.2.,English	
	AS-27X		Color box camera 1/3" SONY CCD 480TVL 0.5Lux/F1.	1000000
	AS-620	 110*70*70	SHARP 1/4"CCD 420TVL 0Lux/F1.2 12pcs IR LED 10-20m 3.6mm Lens	450000
	PR-668		SHARP 1 LED 10-20m 3.6mm Le /4"CCD 420TVL 0Lux/F1.2 12pcs IR	600000
	AS-849A		<b>Adjust varifocal IR Cameras 1/3"SONY CCD 480TVL 0.5Lux/F1.2 30pcs IR LED 50m 4-9mm Lens with bracket</b>	850000

	AS-638		<b>IR waterproof 2 glass camera 1/3"SONY CCD 480TVL 0Lux/F1.2 24pcs IR LED 20m 3.6mm Lens</b>	570000
	AS-639A	 140*70*70	IR waterproof 2 glass camera 1/3"SONY CCD 480TVL 0Lux/F1.2 24pcs IR LED 20m 6mm Lens	550000
	AS-639B		IR waterproof 2 glass camera 1/4"SHARP CCD 420TVL 0Lux/F1.2 24pcs IR LED 20m 3.6mm Lens	450000
	<b>AS-649C</b>		<b>1/3SONY CCD 480TVL-0.5Lux/F1.2 30pcs IR LED 40m 6mm Lens</b>	600000
	AS-635A	 130*75*75	IR waterproof 2 glass camera 1/3"SONY CCD 480TVL 0Lux/F1.2 24pcs IR LED 40m 3.6mm Lens	
	JK207		IR waterproof 2 glass camera 1/3"SONY CCD 420TVL 0Lux/F1.2 24pcs IR LED 40m 3.6mm Lens WITH BRAKET	480000
	AS-635B		IR waterproof 2 glass camera 1/4"Sharp CCD 420TVL 0Lux/F1.2 24pcs IR LED 40m 3.6mm Lens	
	<b>W232E7</b>		<b>IR waterproof 2 glass camera 1/3"SONY CCD 480TVL 0.5Lux/F1.2 18pcs IR LED 30m 3.6mm Lens</b>	600000
	AS-640A	 180*100*100	IR waterproof camera 1/3"SONY CCD 480TVL 0Lux/F1.2 30pcs IR LED 60m 12mm Lens	850000
	AS-640B		IR waterproof camera 1/4"SONY CCD 420TVL 0Lux/F1.2 30pcs IR LED 50m 12mm Lens	650000
	JK-504		IR waterproof camera 1/3"SONY CCD 420TVL 0Lux/F1.2 30pcs IR LED 80m 12mm Lens	1100000
	<b>AS-66D</b>		<b>waterproof IR Camera 1/3"SONY CCD 420TVL 0.5Lux/F1.2 34pcs IR LED 8mm Lens 60m</b>	900000
	AS-XP16RX	 195*110*140	16mm fixed Lens 1/4"sony CCD 420TVL 0.5Lux/F1.2 36pcs IR LED	600000
	C 542H		16mm fixed Lens 1/4"SHARP CCD 420TVL 0Lux/F1.2 36pcs IR LED	
SMOKE CAMERA	AS-616	 130*130*60	Smoke detector camera 1/4"SHARP CCD 420TVL 1.0Lux/F1.2 3.6mm Lens	390000
	C 203		Smoke detector camera 1/3"sony CCD 420TVL 1.0Lux/F1.2 3.6mm Lens	440000
MINI CAM	C101		Color mini camera 1/3"sony CCD 480TVL 0.5Lux/F1.2 3.6mm Lens	480000
	M232B2			
	AS-661		Color mini camera 1/3"SONY CCD 420TVL 1.0Lux/F1.2 3.6mm Lens Pinhole	350000

ERA				
QUAD	WK404M		Color Four Channel Real time Quad Processor Replay single picture 2 zoom Imageresolution:720×576 (PAL) Video input:4CH, Video output:1CH VCR input:1CH, VCR output:1CH	
	WK-804M		Color Four Channel Real time Quad Processor Replay single picture 2 zoom Imageresolution:720×576 (PAL) Video output:1CH VCR input:1CH, VCR output:1CH Video input:4CH,	
WIRELESS CAMERA	WS-309AS		1.2G Small Wireless Color Cmos Camera Technical Parameters of Transmitting Unit Sensitivity: +18DB-AGL ON-OFF Wireless Audio Receiver Receiving Frequency:1.2G/2.4G Receiving Signal:Video,Audio	750000
Speed dome	AS-98C		480TVL, F=3.6~98mm,27x optical & 10 digital, HITACHI,52°(W)-2.6°(T), PAL: 752(H)*582(V) NTSC: 768 x 494, Auto White Balance, ON/OFF SWITCHABLE,128PRESET, More than 48dB 7"	7000000
MINI SPEED DOME	AS-18A		Mini Outdoor High speed dome camera SAMSUNG 10X optical zoom, 0.01Lux/F1.2 PELCO-D and PELCO-P,RS-485 Pan speed:0.5°-300°/S,Tilt speed:0.5°-180°/S -40°C+60°C,OSD menu	520000

CAMERA ACCESSORIES

<p>ADAPTOR</p>	<p>WITH CABLE</p>	 <p>27000</p> <p>12V – 1A 1.50m cable</p>	<p>WITHOUT CABLE</p>	 <p>32000</p> <p>12V-1A</p>
<p>پایه دوربین مدار بسته</p>	<p>C3</p>	 <p>15000</p> <p>8.5(H)MM*4.5MM(w)</p>	<p>C7</p>	 <p>16.5CM(H)*8.5(W)</p>
	<p>C8</p>	 <p>20000</p> <p>14cm(h)5.8cm(w)</p>	<p>C10</p>	 <p>25000</p> <p>6.5cm(w)*16.5cm(h)</p>
	<p>C15</p> <p>50000</p>	 <p>30cm(H)*8.5cm(w)</p>	<p>C16</p>	 <p>115mm*215mm</p>
	<p>C18</p> <p>60000</p>	 <p>180mm*300mm</p>	<p>C5</p>	 <p>30000</p>
<p>RS Convertor</p> <p>150000</p>			<p>BNC</p> <p>4000</p>	

